

Build For Your Business  
Meet All Your Needs


**WIMI**sys

# PT 51

## Features

- 15" PCAP Touchscreen
- IP54 Water and Dust Resistant Front Panel
- Intel Bay Trail Processor ( Fanless design )
- 3 Track MSR Available
- VESA Mount Compliant
- 2<sup>nd</sup> 15" Display and Customer Display Available

## Application



The state-of-the art of PT51 present stylish and modern design POS system. The cutting edge of mechanical design such as hidden cable and hidden power adapter are space saving and easy to manage counter space. The fanless design PT51 guarantees stability and high performance to enhance customer experience. Seamless integration of various peripheral modules such as MSR, Second Display and Customer Display are available to meet all customer requirement.



# PT 51

Build For Your Business  
Meet All Your Needs

**WIMISYS**

## Specifications



<b>System</b>	Motherboard Processor Chipset System Memory Storage Device Graphic Engine	MB-36 Intel Bay Trail CPU Celeron J1900, up to 2.4GHz CPU Integrated 1 x DDR3L SO-DIMM up to 8GB 1 x 64 GB SSD (M.2 B) Intel HD Graphic DX11 and OCL1.1
<b>LCD Touch Panel</b>	LCD Size Brightness Resolution Touch Screen	15" TFT LCD 300 nits 1024 x 768 True-Flat PCAP Multi-touch
<b>Expansion</b>	Mini PCI-E Slot M.2 .B Slot	1 1
<b>External I/O Ports</b>	USB Serial Port LAN Cash Drawer VGA DC Jack Power Button	1 x USB3.0, 7 x USB 2.0 1 x DB-9 (COM1) 1 x RJ-45 (10/100/1000 baseT) 1 x RJ-11 (2 In / 2 Out) 1 x DB-15 1 x 2-pin 1
<b>Optional I/O</b>	Serial Port	2 x DB-9 (COM2-3)
<b>Audio</b>	Internal Speaker	1 x 2W (Option)
<b>Indicator</b>	Power LED	1
<b>Power</b>	Power Adapter	60W / 12V
<b>Peripheral (Option)</b>	MSR iButton Customer Display 2nd Display	3-Track MSR (USB) iButton (USB) LCM display 2 x 20 characters (USB) 11.6" / 1366 x 768 (VGA) 15.1" / 1024 x 768 (VGA)
<b>Mounting (Option)</b>		VESA Mount 75 x75 / 100 x 100 mm
<b>Certificate</b>	EMC & Safety	BSMI/CCC/CE/FCC Class A / ESD: Air 8kV ; Con 4kV/ LVD
<b>Environment</b>	Operating Temperature Storage Temperature Humidity	0°C ~ 35°C (32°F ~ 95°F) -20°C ~ 60°C (-4°F ~ 140°F) 20% ~ 80% RH non-condensing
<b>Dimensions (WxDxH)</b>		360 x 199 x 330 mm
<b>Weight</b>		5.01 kgs
<b>OS Supported</b>		Windows 7, POSReady 7, Windows Embedded 8.1 Industry, Windows 10 IoT, Linux

**WIMISYS**

Tel: 86-755-2733 7509  
Fax: 86-755-2733 7931  
www.wimisis.com

E-mail: sales@wimisis.com

Address: Room 3A01, Building A, Tongxin Technology Mansion, No 6261 in Baoan Road,  
Qiaotou Community, Fuhai Street, Baoan District, Shenzhen 518103, China



2004227751

© 2020 WIMISYS All rights reserved. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. WIMISYS endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of WIMISYS products and services is continuous, and published information may not be up to date. It is important to check the current position with WIMISYS.

